

JP Series

Conduit Mounted Underwater Junction Box



Construction: Cast bronze with stainless steel fasteners.


Grounding: Internal grounding lug for each fixture.

Gasket: Black neoprene rubber.

Cord Seals: Factory installed, machined brass, compression type, for 16-3 or 10-3 Type STOW cord.

Safety: Underwriters Laboratories Listed for underwater and dry applications.

Optional: Schedule 40 red brass conduit riser with integral waterstop and grounding lug, add suffix **-WS** to catalog number.



Model Number	Dimensions			Bottom Taps		Side Taps	
	A	B	C	Qty	Size*	Qty	Size
JP-7-(*)-(†)-(+)	4"	4"	3 ⁵ / ₁₆ "	1	1/2", 3/4"	1 to 4	1/2", 3/4"
JP-7-2-(*)-(†)-(+)	4"	4"	3 ⁵ / ₁₆ "	2	3/4"	1 to 4	1/2", 3/4"
JP-8-(*)-(†)-(+)	5 ¹ / ₄ "	5 ¹ / ₄ "	3 ⁵ / ₁₆ "	1	3/4", 1"	1 to 8	1/2", 3/4"
JP-9-(*)-(†)-(+)	5 ¹ / ₄ "	5 ¹ / ₄ "	3 ³ / ₁₆ "	2	3/4", 1"	1 to 8	1/2", 3/4"
JP-10-(*)-(†)-(+)	6 ⁷ / ₁₆ "	6"	5 ³ / ₈ "	1	3/4", 1", 1 1/2"	1 to 16	1/2", 3/4"

* Specify required size of bottom connections.

† Specify required number of side connections.

+ Specify required size of side connections.

Speaking the language of water.™

