

# LLP-( )A

## Underwater Freestanding

**Fixture Body:** Cast bronze with brass cord compression seal.

**Rock Guard:** Cast bronze, elevated for ease of maintenance.

**Yoke/Base:** Cast bronze with red brass riser. 90° angular adjustment on a 360° axis.

**Reflector:** Stamped, polished stainless steel.

**Wiring:** Furnished with ten feet of 16-3 Type STOW submersible cord; entry is totally encapsulated in an epoxy compound.

**Socket:** High temperature, mini-can screw base.

**Lamp:** Per chart. Supplied separately, add suffix **-LP** to catalog number to include lamp.

**Lens Gasket:** High temperature, single piece, molded silicone rubber.

**Lens:** Clear, convex, high temperature tempered glass.


**Safety:** Underwriters Laboratories Listed for underwater application. Supplied with an integral thermal cutoff device.

**Optional:** Colored lenses - red, blue, green, amber, and turquoise available.



100-500 Watts, 120 Volts  
100 Watts, 12 Volts

Model Number	UL Max. Wattage Rating	Lamp Type	Watts	Volts	Lamp Life (Hours)
LLP-100LA	100	T4	100	12	1000
LLP-100HA	100		100	130	2000
LLP-150HA	150		150	130	2000
LLP-250HA	250		250	130	2000
LLP-500HA	500		500	130	2000



Speaking the language of water.™

