FIC Series

Fountain in a Can [™] - Bubbler

Water Effect:

A simple pulsing mound of highly aerated water.

Construction:

Single piece, type 304 deep-drawn stainless steel housing with a 1" FPT inlet, grounding connection, cast bronze top cover, EPDM 70 durometer o-ring, 18/8 stainless steel fasteners, and 11" diameter cast bronze top plate. Unit is supplied with a high density polyethylene (HDPE) construction cover, three 3/8" x 12" x 2" stainless steel anchor bolts with leveling nuts and washers, and a wood template.

Nozzle:

Precision machined brass.

Finish:

Standard finish is Natural Bronze.


Optional finishes - Dark Bronze (DB), or Verde Green (VG).

Contact factory for custom finishes.





Details							
Model Number	Top Diameter	Inlet FPT	Feet	Spray Height			
				1	1.5	2	2.5
FIC-B1100	11"	1½"	GPM	42	45	50	58
			Head Ft.	10	11	12	17
			Spread Ft.	1	1.5	1.75	2



NOZZLE REQUIREMENTS:

- 1. Nozzle requires fine screening for debris removal. #8 (3/32") minimum mesh or smaller.
- 2. Housing must be encapsulated in concrete.
- 3. One 1" FTP connection point. Fittings by installer.

2021-01

